STOREFRONT

Design Guideline Checklist

- + Meets Guidelines
- Does Not Meet Guidelines
- +/- Meets Guidelines with Conditions as Noted
- NA Not Applicable
- NSI Not Sufficient Information

	Guideline	Finding	Comment
OT74	Do not remove historic materials from storefronts. Such materials as	rmaing	Comment
SF1	wood, cast iron, terra cotta, carrara glass, ceramic tile, and brick		
	contribute significantly to a storefront's architectural character.		
SF2	Use historic materials where historic storefronts must be replaced in		
Sr 2	part of in whole. Cast iron, limestone, or wood are appropriate		
	materials for storefront replacement.		
SF3	Retain all historic storefront elements, including later alterations that		
DI J	are historic in their own right. An example is a late nineteenth-		
	century storefront with Art Deco features added during the 1930s.		
SF4	Respect façade alterations that have attained historic or architectural		
DI T	significance in their own right. Work to incorporate such elements		
	into any new storefront design or renovation. Do not attempt to		
	recreate a conjectural historic design if there is insufficient physical		
	or documentary evidence.		
SF5	Do not remove later historically-significant material to restore a		
	building to an earlier period. For example, a 1910 storefront should		
	not be taken back to a conjectural 1850s appearance.		
SF6	Maintain the original scale, proportion, and organization of		
	architectural elements (bulkheads, display windows, transoms, door,		
~	piers, and cornices) when renovating historic storefronts.		
SF7	Use the original form and detailing of a storefront as a model, if extensive deterioration requires complete reconstruction. The		
	reconstruction should convey the same visual appearance and use the		
	same material as the original. Under no circumstances should a		
	historic storefront be removed and not replaced.		
CTO	Use historic, pictorial, and physical documentation to construct a		
SF8	historic storefront when the original is missing. The design may be		
	an accurate restoration, if sufficient evidence exists, or a new design		
	that is compatible with the size, scale, material, and color of the		
	historic building and district.		
SF9	Keep storefront designs within their original openings. Transitions		
D1 /	from one façade to another should be clean and clearly defined.		
SF10	Emphasize the transparent character of storefronts when		
2220	implementing new designs or renovations. Generally, 60 percent of		
	the wall surface at the sidewalk level should be transparent.		
	Historically, merchandise seen in storefront displays was emphasized	4	
OTC44	to a much greater extent than any ornament on the storefront itself.	-	
SF11	Do not apply reflective or insulating film to window glass.		
SF12	Do not use smoked, tinted, low-E, or reflective glass on building		
	facades that can be seen from a public way.		
SF13	Use large sheets of clear glass when replacement of storefront		
	display windows is required.		
SF14	Select replacement doors that reflect the storefront's original		
	character. Doors should have large glass panels and be made of		
	wood or painted steel or aluminum. They should not be overly-		
	decorated or possess inappropriate historic features.		

SF15	Do not change or reorient the location of the main entrance of a storefront.	
SF16	Design awnings to complement existing architectural features. They should not overwhelm the façade.	
SF17	Install awnings made out of matte-finish weather-proofed fabric or a traditional form. Fiberglass, metal, plastic, and back-lit awnings that have contemporary shapes are inappropriate and visually intrusive.	
SF18	Select an awning color that complements the building, with solid colors and narrow or wide stripes running perpendicular to the building being the preferred patterns.	
SF19	Install awnings in a way that does not harm the building. Hardware installation should be limited to that which is required for structural stability and should be driven into mortar joints rather than into masonry.	
SF20	Attach awnings between the window display area and the signboard or second-floor window sills. Awnings should be attached below the transom line where historic prism glass is present.	
SF21	Install awnings so that the valance is no lower than 7'-6" above the sidewalk.	
SF22	Maintain the commercial character of storefronts, even if they have changed use. Blinds or insulating curtains may be added for privacy and thermal performance.	
SF23	Design replacement storefronts that are compatible with and complementary to their historic neighbors, but are recognizable as being of their own era.	
SF24	Do not add elements to storefronts that have no historic precedent. Common examples of inappropriate alterations include the installation of coach lanterns, false mansard designs, small-paned windows, and inoperable shutters.	
SF25	Do not add false fronts, false stories, or pent eaves to the roofs of commercial buildings.	
SF26	Do not use storefront design elements that are historically inappropriate, such as small-pane windows or colonial doors on latenineteenth and twentieth-century buildings.	
SF27	Do not use materials in storefront renovations that were not available at the time of original construction, such as vinyl or aluminum siding, stainless steel, uncoated anodized aluminum, tinted glass, or artificial stone.	
SF28	Use historic materials when replacement of bulkheads is required in part or in whole. Wood or stone panels are most appropriate.	
SF29	Do not use rough-textured wood siding or simulated masonry, such as permastone, on storefronts.	
SF30	Use historic materials when cornice replacement is required in part of in whole. Cast iron, wood, or sheet metal area appropriate materials.	
SF31	Do not install inappropriately-scaled signs that obscure or damage surviving storefront features that convey a building's architectural character.	
SF32	Include the following storefront elements when redesigning or renovating a historic storefront: large display windows and doors, transoms, relatively thin framing elements, a cornice element separating the storefront from the upper façade, low bulkheads, and tile entry flooring.	
SF33	Photographically document architectural features that are slated for reconstruction prior to the removal of any historic fabric.	